



## PRODUCT GROUP 10

### Series 10-03839

Thickening powder



Auxiliary agent to enhance the viscosity and increase the thixotropy properties. Universal useable thickening powder for all solvent based screen and pad printing inks, also applicable for UV-curable systems.



#### SUBSTRATES

Complete spectrum



#### USE

##### Application

Easy to mix thickening powder for all ink technologies. Increase the viscosity and thixotropy of screen and pad printing systems.



#### PROPERTIES, PROCESSING, DRYING AND MESH

##### Mesh

-

##### Drying / Curing

No influence

##### Further Processing

-



#### ADDITIVES

| Name | Series 10-03839 | Addition Ratio | 1% - 3%, max 5% |
|------|-----------------|----------------|-----------------|
|------|-----------------|----------------|-----------------|



#### VARIOUS

##### Delivery Conditions

In stock

##### Other

Stir well the modified ink before use



#### Disclaimer

Please thoroughly read the Material Safety Data Sheet (MSDS) prior to processing. The Material safety Data Sheets according to 91/155/EWG form, contain indications of hazardous ingredients. Exposure levels and instructions for precautions when processing, handling and storing as well as first aid. The information given in the MSDS refer to the processing as described within this technical leaflet. Above data are based on laboratory tests and field experience. All therein contained statements are to the best of our knowledge without any obligation from our side and do not discharge from testing the product by yourself. In doubtful cases, you are kindly requested to either perform your own tests or refer to our technical staff. Application, use and processing of the delivered products are beyond our control and are therefore at your own risk and responsibility. Printcolor is thus free from any guarantees or liabilities. In cases of justified complaints, Printcolor can only be made liable for the counterpart of the utilized ink system. Adding not stated products or foreign / competitors products, is solely at your own risk and liberates Printcolor of any later calls; especially in cases when damages occurred and which have been caused through use of products of foreign type. This leaflet replaces all former issues. (02/2008)



**H. W. SANDS CORP.**

1003 W. Indiantown Road • Suite 215 • Jupiter, FL 33458  
Telephone: (561) 743-8090 • Facsimile - (561)743-4088  
Website: [www.hwsands.com](http://www.hwsands.com)