



PRODUCT GROUP 140

Series 140-15009

Solvent Based Adhesive, removable



The special adhesive, Series 140-15009 belongs to the category of "none-permanent" adhesives. This means, it can easily be removed after temporary use. Applications are production of adhesive foils and labels which do not have to fulfill high mechanical resistances and will have to be removed easily and without any residues. Besides timely limited applications as for example adhesive for window decors, it can also be used as an alternative for "Letraset", transfer labels, a. s. o.

The ready-to-use formula does not have to be diluted and can immediately be processed with the screen printing installation on hand. Optimal printability of the adhesive is achieved at 20°C; yet, the possible temperatures for application lie between 20-28°C. Thickness of the adhesive layer can however be influenced by the chosen mesh. The adhesive must be absolutely dry before covered with a protective paper.



SUBSTRATES

PET-foils	Soft-PVC	Rigid-PVC	Papers
-----------	----------	-----------	--------



USE

Application	Décor foils, Letraset, transfers
-------------	----------------------------------



PROPERTIES, PROCESSING, DRYING AND MESH

Mesh	24-140 Y PW PET 1000 up to 77-55 Y PW PET 1000
Drying / Curing	Jet / Air
Further Processing	Punching, cutting



ADDITIVES

Thinner	Press-ready	Addition Ratio	-
Retarder	Press-ready	Addition Ratio	-



VARIOUS

Delivery Conditions	1 kg / 5 kg / 25 kg
Other	-



Disclaimer

Please thoroughly read the Material Safety Data Sheet (MSDS) prior to processing. The Material safety Data Sheets according to 91/155/EWG form, contain indications of hazardous ingredients. Exposure levels and instructions for precautions when processing, handling and storing as well as first aid. The information given in the MSDS refers to the processing as described within this technical leaflet. Above data are based on laboratory tests and field experience. All therein contained statements are to the best of our knowledge without any obligation from our side and do not discharge from testing the product by yourself. In doubtful cases, you are kindly requested to either perform your own tests or refer to our technical staff. Application, use and processing of the delivered products are beyond our control and are therefore at your own risk and responsibility. Printcolor is thus free from any guarantees or liabilities. In cases of justified complaints, Printcolor can only be made liable for the counterpart of the utilized ink system. Adding not stated products or foreign / competitors products, is solely at your own risk and liberates Printcolor of any later calls; especially in cases when damages occurred and which have been caused through use of products of foreign type. This leaflet replaces all former issues. (03/2009)



H. W. SANDS CORP.

1003 W. Indiantown Road • Suite 215 • Jupiter, FL 33458
Telephone: (561) 743-8090 • Facsimile - (561)743-4088
Website: www.hwsands.com