




PRODUCT GROUP 500

Series 500-033

UV-Accelerator



This UV-additive Series 500-033 increase the reactivity (polymerization speed) of UV-curable inks. Especially when modifying highly pigmented color shades the curing speed and efficiency will be improved. This special additive is a optimized cocktail of highly active initiators and universal useable. Furthermore, positive effects in regards to adhesion on various substrates can occur because of the stronger bonding in the curing process when adding up to 5-10% by weight or more.



SUBSTRATES

-



USE

Application UV-inks in general (mix thoroughly)



PROPERTIES, PROCESSING, DRYING AND MESH

Mesh -

Drying / Curing -

Further Processing -



ADDITIVES

Thinner	Series 500-033	Addition Ratio	5-10 % by weight
----------------	----------------	-----------------------	------------------

Retarder	-	Addition Ratio	-
-----------------	---	-----------------------	---



VARIOUS

Delivery Conditions 1 kg / 5 kg

Other Protect from direct light



Disclaimer

Please thoroughly read the Material Safety Data Sheet (MSDS) prior to processing. The Material safety Data Sheets according to 91/155/EWG form, contain indications of hazardous ingredients. Exposure levels and instructions for precautions when processing, handling and storing as well as first aid. The information given in the MSDS refers to the processing as described within this technical leaflet. Above data are based on laboratory tests and field experience. All therein contained statements are to the best of our knowledge without any obligation from our side and do not discharge from testing the product by yourself. In doubtful cases, you are kindly requested to either perform your own tests or refer to our technical staff. Application, use and processing of the delivered products are beyond our control and are therefore at your own risk and responsibility. Printcolor is thus free from any guarantees or liabilities. In cases of justified complaints, Printcolor can only be made liable for the counterpart of the utilized ink system. Adding not stated products or foreign / competitors products, is solely at your own risk and liberates Printcolor of any later calls; especially in cases when damages occurred and which have been caused through use of products of foreign type. This leaflet replaces all former issues. (07/2009)



H. W. SANDS CORP.

1003 W. Indiantown Road • Suite 215 • Jupiter, FL 33458
Telephone: (561) 743-8090 • Facsimile - (561)743-4088
Website: www.hwsands.com