



PRODUCT GROUP 600

Series 665-33/369

Floor coating, gray, ready-to-use



This paint has specially been developed for floor coatings in the color shade "RAL 7037 Dust gray". The used binders are meeting the highest requirements in respect to durability and longevity of industrial floors and are beside that, easy to handle. Before use, the system just has to be mixed with hardener, Series 600-HDA (addition/mixing ratio 5:1). After mixing of both components, application under normal conditions is at least guaranteed for 8 hours. Bonding requires temperatures of > 18°C. The area which wishes to be coated has to be free of dust and dirt.



SUBSTRATES

Floors	Stone	Coatings
--------	-------	----------



USE

Application	Floor coatings
-------------	----------------



PROPERTIES, PROCESSING, DRYING AND MESH

Mesh	Rolling, painting
Drying / Curing	Air drying (> 18°C, ideally 23-25°C)
Further Processing	-



ADDITIVES

Thinner	Set application-ready	Addition Ratio	-
Retarder	Series 600-743	Addition Ratio	> 10% by weight



VARIOUS

Delivery Conditions	1kg / 5kg / 25 kg
Other	Hardener, Series 600-HDA, addition ratio 20% by weight Stir well before use



Precautionary measures

Read material safety data sheet prior to processing. The material safety data sheets according to OSHA form contain indication of hazardous ingredients, TLV-level and instructions for precautions when processing, handling and storing as well as first aid. The information given in the MSDS refers to processing as described in this technical leaflet. The statements in our leaflets have been made to the best of our knowledge and are given without any obligation. They serve to advise our business associates, but it is absolutely necessary to make your own printing tests under local conditions, with regard to the intended purpose prior to starting the printing job. In case of any doubts please contact our technical advisors. The application, use and processing of the products delivered by us are beyond our control. This is subject to your responsibility and there is no liability or guarantee on our part. In case of justified complaints the manufacturer can only be made liable for the countervalue of the used ink system. Addition of not mentioned products or competitors products are on your own risk and releases Printcolor Screen Ltd. of any later demands, especially in cases of damage and loss caused by alien products. All former leaflets are no longer valid. (07/2009)



H. W. SANDS CORP.

1003 W. Indiantown Road • Suite 215 • Jupiter, FL 33458
Telephone: (561) 743-8090 • Facsimile - (561) 743-4088
Website: www.hwsands.com