



PRODUCT GROUP 700

Series 700-032

Anti-static paste



Anti-static paste series 700-032 has been developed to solve static problems in pad printing. An addition of 5 % of the anti-static paste 700-032 reduces or even completely eliminates effects like „spider webbing“. Unfavorable conditions (low humidity, easily electrostatic chargeable material, a.s.o.) allow an addition of up to 20 % by weight of this special paste to the ink. Anti-static paste series 700-032 is suitable for all pad printing inks of product group 700 and has no influence to the adhesion of the ink.



SUBSTRATES

-



USE

Application

-



PROPERTIES, PROCESSING, DRYING AND MESH

Mesh

-

Drying / Curing

-

Further Processing

-



ADDITIVES

Thinner

-

Addition Ratio

-

Retarder

-

Addition Ratio

-



VARIOUS

Delivery Conditions

1 kg / 5 kg / 25 kg

Other

Addition ratio: 5-20 % by weight



Disclaimer

Please thoroughly read the Material Safety Data Sheet (MSDS) prior to processing. The Material safety Data Sheets according to 91/155/EWG form, contain indications of hazardous ingredients. Exposure levels and instructions for precautions when processing, handling and storing as well as first aid. The information given in the MSDS refer to the processing as described within this technical leaflet. Above data are based on laboratory tests and field experience. All therein contained statements are to the best of our knowledge without any obligation from our side and do not discharge from testing the product by yourself. In doubtful cases, you are kindly requested to either perform your own tests or refer to our technical staff. Application, use and processing of the delivered products are beyond our control and are therefore at your own risk and responsibility. Printcolor is thus free from any guarantees or liabilities. In cases of justified complaints, Printcolor can only be made liable for the counterpart of the utilized ink system. Adding not stated products or foreign / competitors products, is solely at your own risk and liberates Printcolor of any later calls; especially in cases when damages occurred and which have been caused through use of products of foreign type. This leaflet replaces all former issues. (11/2008)



H. W. SANDS CORP.

1003 W. Indiantown Road • Suite 215 • Jupiter, FL 33458
Telephone: (561) 743-8090 • Facsimile - (561)743-4088
Website: www.hwsands.com