



PRODUCT GROUP XXX

Series xxx-969/xx Blackboard-Inks



These special screen printing inks have purposefully been designed for the classic "black-board" applications. A durable and long-lasting coating can be created on suitable substrates which is reversible and can be written onto with chalk on a long term basis. In such way, the characteristically whole-area or partial marking-fields can be created for displays or gastronomic signs. They are convincing by their good adhesion of chalk and unproblematic cleaning (water or dry). In accordance with the substrate and a proper handling, this system can easily be applied for outdoor use.

Besides black, almost all desired color shades of blackboard inks can be realized with this technology. The Printcolor blackboard inks are available in different series (solvent based or UV-curable). For example Series 320-969/33 (ST-black), Series 388-969/31 (ST-signal green) or Series 560-969/33 (ST-black).



SUBSTRATES

Soft- and rigid PVC	Coated Polyester	Paper, paperboards, cardboards
Polycarbonate	Coatings	Polystyrene, ABS and SAN



USE

Application	Primarily indoor-use, temporarily outdoor-use
--------------------	---



PROPERTIES, PROCESSING, DRYING AND MESH

Mesh	77-55 Y PW PET 1000
Drying / Curing	Depending on series
Further Processing	Punching, cutting, embossing



ADDITIVES

Thinner	Depending on series	Addition Ratio	-
Retarder	Depending on series	Addition Ratio	-



VARIOUS

Delivery Conditions	1 kg / 5 kg / 20 kg, resp. 25 kg (depending on series)
Other	Stir well before use



Disclaimer

Please thoroughly read the Material Safety Data Sheet (MSDS) prior to processing. The Material safety Data Sheets according to 91/155/EWG form, contain indications of hazardous ingredients. Exposure levels and instructions for precautions when processing, handling and storing as well as first aid. The information given in the MSDS refers to the processing as described within this technical leaflet. Above data are based on laboratory tests and field experience. All therein contained statements are to the best of our knowledge without any obligation from our side and do not discharge from testing the product by yourself. In doubtful cases, you are kindly requested to either perform your own tests or refer to our technical staff. Application, use and processing of the delivered products are beyond our control and are therefore at your own risk and responsibility. Printcolor is thus free from any guarantees or liabilities. In cases of justified complaints, Printcolor can only be made liable for the counterpart of the utilized ink system. Adding not stated products or foreign / competitors products, is solely at your own risk and liberates Printcolor of any later calls; especially in cases when damages occurred and which have been caused through use of products of foreign type. This leaflet replaces all former issues. (07/2009)



H. W. SANDS CORP.
1003 W. Indiantown Road • Suite 215 • Jupiter, FL 33458
Telephone: (561) 743-8090 • Facsimile - (561)743-4088
Website: www.hwsands.com